



HUSQVARNA 525LST

Powerful trimmer with a high torque gear box. The machine has a robust construction with durable components and is easy to maintain - all to give you trouble-free use. The patented X-Torq® engine gives you more power, less fuel consumption and less exhaust emissions compared to a conventional engine.



Intuitive controls
The choke and purge are easy to reach and understand.




Auto return stop switch
Stop switch automatically resets to the ON position for trouble-free starting.



X-Torq® engine
The X-Torq® engine design reduces harmful exhaust emissions by up to 75% and increases fuel efficiency by up to 20%.



Easy starting
Air purge for very easy starting.



Hard chromium
Hard chromium plated cylinder bore provides increased durability and extended product life.



Optimum comfort
Soft-grip handles for optimum comfort. The handle makes it easy to turn and use at different angles.

Additional features

Stand alone starter

The stand alone starter makes it easy to change starter cord if needed.

High torque bevel gear

Bevel gear designed with high torque and the cutting equipment parallel to the ground for best cutting performance.

Tap 'N Go™ trimmer head

Twin line cutting system with Tap 'N Go™ for quick line feed.

Commercial grade 2-stage air filter

The commercial grade 2-stage air filter reduces servicing costs and also results in less engine wear.

Adjustable harness hook eyelet

Adjustable eye let for best balance

Technical data

Engine specification

Cylinder displacement	1.55 cu.inch / 25.4 cm ³
Cylinder bore	1.34 inch / 34 mm
Cylinder stroke	1.1 inch / 28 mm
Power output	1.34 hp / 1 kW
Maximum power speed	8500 rpm
Fuel tank volume	17.25 fl oz / 0.51 lit
Fuel consumption	520 g/kWh

Technical data

Ignition module air gap	0.01 " / 0.3 mm
Idling speed	3000 rpm
Spark plug	NGK BPMR8Y
Electrode gap	0.03 " / 0.65 mm
Torque, max.	1.2 Nm/6000 rpm
Clutch engagement speed	4000 rpm (± 120 rpm)
Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
Maximum rpm output shaft	5500 rpm

Vibration & noise data

Equivalent vibration level (ahv, eq) left / right handle	5.8/3.3 m/s ²
Sound pressure level at operators ear	98 dB(A)
Sound power level, guaranteed (LWA)	114 dB(A)

Transmission data

Gear ratio	1:1.46
Drive gear angle	30 °

Overall dimensions

Weight (excl. cutting equipment)	10.36 lbs / 4.7 kg
Tube length	58.39 inch / 1483 mm
Tube diameter	0.94 " / 24 mm

Logistical data

Product size, LxWxH	70.43x9.53x8.98 inch / 178.9x24.2x22.8 mm
---------------------	---