



HUSQVARNA 322L

This quality trimmer is an exciting addition to the Husqvarna range. Targeted at high end domestic end users and including many of the quality features of the 500 series trimmers this unit offers high performance, ease of use and super value for money. A long one piece straight shaft allows easy trimming of edges, under shrubs and along fences.



Intuitive controls

The choke and purge are easy to reach and understand.



Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.




X-Torq® engine

The X-Torq® engine design reduces harmful exhaust emissions by up to 75% and increases fuel efficiency by up to 20%.



Easy starting

Air purge for very easy starting.



Hard chromium

Hard chromium plated cylinder bore provides increased durability and extended product life.



Stand alone starter

The stand alone starter makes it easy to change starter cord if needed.

Additional features

Easy to use trimmer head

Easy to use Tap 'N Go™ dual line trimmer head. Easy to refill.

Commercial grade 2-stage air filter

The commercial grade 2-stage air filter reduces servicing costs and also results in less engine wear.

Tap 'N Go™ trimmer head

Twin line cutting system with Tap 'N Go™ for quick line feed.

Heavy duty bevel gear

Transmission and bevel gear in proven design together with a sturdy trimmer head for trouble free work.

High torque bevel gear

Bevel gear designed with high torque and the cutting equipment parallel to the ground for best cutting performance.

Technical data

Engine specification

Cylinder displacement	1.37 cu.inch / 22.5 cm ³
Cylinder bore	1.26 inch / 32 mm
Cylinder stroke	1.1 inch / 28 mm
Power output	1.01 hp / 0.75 kW
Maximum power speed	8500 rpm
Fuel tank volume	16.91 fl oz / 0.5 lit
Fuel consumption	540 g/kWh

Technical data

Ignition module air gap	0.01 " / 0.3 mm
Idling speed	3000 rpm
Spark plug	NGK BPMR8Y
Electrode gap	0.03 " / 0.65 mm
Torque, max.	1 Nm/6000 rpm
Clutch engagement speed	4000 rpm (± 120 rpm)
Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
Maximum rpm output shaft	6200 rpm
Output shaft thread	M10x1.25V

Vibration & noise data

Equivalent vibration level (ahv, eq) left / right handle	5.4/4 m/s ²
Sound pressure level at operators ear	98 dB(A)
Sound power level, guaranteed (LWA)	107 dB(A)

Transmission data

Gear ratio	1:1.46
Drive gear angle	30 °

Equipment

OEM Trimmer head	--
------------------	----

Overall dimensions

Weight (excl. cutting equipment)	9.26 lbs / 4.2 kg
Tube length	58.39 inch / 1483 mm
Tube diameter	0.94 " / 24 mm

Logistical data

Weight incl. packaging	18 lbs / 8.16 kg
Product size, LxWxH	69.76x8.9x8.9 inch / 177.2x22.6x22.6 mm
Packaging size, LxWxH	71.65x11.02x9.45 inch / 1820x280x240 mm

Accessories